CITY SCAN
TECH



Intelli Plus Series


CS-IAI+T8M2.8

8 MP AI Turret Network Camera

4K 8 MP AI turret with a 2.8 mm wide-angle lens, up to 30 m IR, face recognition and the full edge-analytics suite in an IP67 metal housing.

COVERAGE

2.8 MM · 105° HFOV · 30 M IR



AI HIGHLIGHTS

- Face recognition
- Pedestrian & vehicle
- Line crossing & intrusion
- Heat map & crowd density

8MP 8 MP 4K Resolution	AI Analytics	Face Recognition	30 m IR Night Vision
105° Wide Angle	Built-in Microphone	PoE Powered	IP67 Weatherproof

KEY FEATURES

- 1/2.8” progressive CMOS, 8 MP 4K
- 3840 × 2160 max resolution
- 2.8 mm fixed lens, F1.6 · 105° HFOV
- Up to 30 m IR · 0.009 lux colour
- Triple-stream H.265 / H.264, up to 16 Mbps
- Edge AI: face recognition, intrusion, LPR, heat map

IDEAL FOR

- Retail stores
- Offices
- Villas
- Warehouses
- Entrances
- Parking areas

© 2026 SAFETY VISION UK · ALL RIGHTS RESERVED

— SECTION 01

Technical Specifications

REFERENCE
CS-IAI+T8M2.8
8 MP · AI

01 Imaging

Image Sensor	1/2.8" Progressive CMOS
Effective Pixels	8 MP · 3840 (H) × 2160 (V)
Min. Illumination	Colour 0.009 lux @ F1.6 (AGC ON) · B/W 0 lux @ IR on
Day / Night	IR-cut filter with auto switch (Day / Night / Auto / Image / Schedule)
Wide Dynamic Range	WDR
Noise Reduction	3D DNR
Backlight Compensation	Off / On (5 zones)
Gain Control	Auto
White Balance	Auto / Manual
Shutter	1/5 – 1/20,000 s
Privacy Masking	Off / On (4 zones, rectangle)
Camera Title	On / Off

02 Lens

Lens Type	Fixed (M12)
Focal Length	2.8 mm
Aperture	F1.6
Field of View	H 105° · V 56° · D 126°
Min. Object Distance	1.8 m

03 Illumination

IR Range	Up to 30 m

07 Electrical

Power Supply	DC 12 V / PoE (IEEE 802.3af)
Power Consumption	DC 12 V max 4.8 W · PoE (48 V) max 6.1 W

08 Mechanical

Dimensions (H × W × D)	100 × 100 × 90 mm
Weight	415 g
Body Material	Metal
Ingress Protection	IP67

04 Video

Compression	H.265 / H.264
Main Stream	@ 30 fps: 8MP (3840×2160) · 5MP (2592×1944, 3072×1728) · 4MP (2592×1520) · 3MP (2304×1296) · 1080P (1920×1080) · 960P (1280×960) · 720P (1280×720)
Sub Stream	@ 30 fps: 1080P (1920×1080) · 720P (1280×720) · VGA (640×480)
Mobile Stream	@ 30 fps: VGA (640×480) · QVGA (320×240)
Bitrate	256 Kbps – 16 Mbps
Bitrate Control	CBR / VBR
Streaming	Triple-stream (Main / Sub / Mobile) · Unicast / Multicast
Motion Detection	Off / On (8 levels)

05 Audio & Smart

Audio	Built-in microphone
Alarm	N/A
Edge Storage	MicroSD slot, up to 256 GB
Hardware Reset	Yes
AI Analytics	Face Recognition · Pedestrian & Vehicle · Perimeter Intrusion · Line Crossing · Object Detection · Crossing Counting · Heat Map · Crowd Density · Queue Length · License Plate · Rare Sound · Intrusion · Region Entrance · Region Exiting

06 Network

Ethernet	RJ45 (10/100BASE-T)
Protocols	TCP/IP · HTTP · HTTPS · DHCP · DNS · DDNS · RTP/RTSP · SMTP · NTP · UPnP · SNMP · FTP
Compatibility	ONVIF Profile S / G / T / M
Security	IP address filter · Complex password · Authenticated username & password
Web Browser	IE 10 / 11 · Safari 12.1+ · Firefox 52+ · Chrome 57+ · Edge 79+

09 Environmental

Operating Conditions	−35 °C to +60 °C · ≤ 95% RH


© 2026 SAFETY VISION UK · ALL RIGHTS RESERVED

— SECTION 02

Dimensions, Build & Ordering

DRAWING
ALL UNITS MM
TOL ±0.5

FIG 01 · DIMENSIONAL DRAWING



In the Box

- Turret camera unit
- Self-adhesive mounting template
- Wall plug & screw kit
- Waterproof RJ-45 connector
- Quick-start guide
- Warranty card

Ordering Information

SKU / MODEL CODE
CS-IAI+T8M2.8

Intelli Plus · 8 MP AI Turret, 2.8 mm fixed lens, PoE, IP67

REGULATORY & CERTIFICATIONS

CE · FCC · ROHS · ONVIF

ADDRESS
Safety Vision UK · South Bank, Chelford Road, Siddington, Macclesfield, SK11 9LF

WEB
safetyvision.uk

EMAIL
info@safetyvision.uk

PHONE
+44 7926 689141

© 2026 SAFETY VISION UK · ALL RIGHTS RESERVED